


NPN General Purpose Amplifier



Features

- Capable of 0.2Watts($T_A=25^{\circ}\text{C}$) of Power Dissipation
- Epoxy meets UL-94 V-0 flammability rating
- Halogen free available upon request by adding suffix "HF"
- Moisture Sensitivity Level 1
- Device Marking:

BC817-16W	6A
BC817-25W	6B
BC817-40W	6C

■ Maximum Ratings ($T_A=25^{\circ}\text{C}$ Unless otherwise specified)

Item	Symbol	Value	Unit
Collector-Emitter Voltage	V_{CEO}	45	V
Collector-Base Voltage	V_{CBO}	50	V
Emitter-Base Voltage	V_{EBO}	5.0	V
Collector Current	I_C	0.5	A
Power dissipation	P_D	200	mW
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	625	$^{\circ}\text{C}/\text{W}$
Operation Junction Temperature	T_j	-55 to +150	$^{\circ}\text{C}$
Storage Temperature	T_{stg}	-55 to +150	$^{\circ}\text{C}$



BC817-16W THRU BC817-40W

■ Electrical Characteristics (Ta=25°C unless otherwise specified)

Item	Symbol	Unit	Conditions	MIN	MAX
Collector-Emitter Voltage	V_{CE0}	V	$I_C=10\text{mAdc}$, $I_B=0$	45	
Collector-Base Voltage	V_{CBO}	V	$I_C=10\text{uAdc}$, $I_E=0$	50	
Emitter-Base Voltage	V_{EBO}	V	$I_E=1.0\text{uAdc}$, $I_C=0$	5.0	
Emitter-base Cut-off Current	I_{EBO}	uAdc	$V_{EB}=4.0\text{Vdc}$, $I_C=0$		0.1
Collector-base Cut-off Current	I_{CBO}	uAdc	$V_{CB}=45\text{Vdc}$, $I_E=0$		0.1
DC Current Gain	$h_{FE(1)}$		$I_C=100\text{mAdc}$, $V_{CE}=1.0\text{Vdc}$	100	600
	$h_{FE(2)}$		$I_C=500\text{mAdc}$, $V_{CE}=1.0\text{Vdc}$	40	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	V	$I_C=500\text{mAdc}$, $I_B=50\text{mAdc}$		0.7
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	V	$I_C=500\text{mAdc}$, $I_B=50\text{mAdc}$		1.2

■ Small-signal Characteristics

Item	Symbol	Unit	Conditions	Min	Max
Transition frequency	f_T	MHz	$I_C=10\text{mAdc}$, $V_{CE}=5.0\text{Vdc}$, $f=100\text{MHz}$	100	



■ Classification of h_{FE}

Rank	BC817-16W	BC817-25W	BC817-40W
Range	100-250	160-400	250-600

■ Ordering Information (Example)

Prefered P/N	Packing Code	Unit Weight(g)	Minimum Package(Pcs)	Inner Box Quantity(Pcs)	Outer Carton Quantity(Pcs)	Delivery Mode
BC817-16W THRU BC817-40W	F2	Approximate 0.005	3000	30000	120000	7" reel


■ Characteristics (Typical)






BC817-16W THRU BC817-40W


Collector-Emitter Saturation Voltage




Base-Emitter Saturation Voltage




Base-Emitter On Voltage



Cob/Cib-V_{CB}/V_{EB}




Power Derating Curve






BC817-16W THRU BC817-40W

■ SOT-323 Package Outline Dimensions



TOP VIEW

SIDE VIEW




SIDE VIEW

SYMBOL	DIMENSIONS			
	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.043	0.900	1.100
A1	0.000	0.004	0.000	0.100
A2	0.035	0.039	0.900	1.000
b	0.006	0.016	0.150	0.400
c	0.004	0.010	0.100	0.250
D	0.071	0.087	1.800	2.200
E	0.045	0.053	1.150	1.350
E1	0.085	0.096	2.150	2.450
e	0.026 TYP		0.650 TYP	
e1	0.047	0.055	1.200	1.400
L	0.021 REF		0.525 REF	
L1	0.010	0.018	0.260	0.460
θ	0°	8°	0°	8°

Note:

- All dimensions are in millimeters (mm) unless otherwise specified.
[所有尺寸均以毫米为单位, 除非另有说明]
- General tolerances: $\pm 0.10\text{mm}$ unless otherwise specified.
[通用公差为 $\pm 0.10\text{mm}$, 除非另有说明]
- Dimensions and tolerances per ASME Y14.5M-2018.
[尺寸和公差遵循 ASME Y14.5M-2018 标准]
- All dimensions shown are exclusive of burrs and gate residues.
Burrs and gate vestiges shall not exceed 0.15 mm in maximum.
[所有尺寸均不包括毛刺和浇口残留。毛刺与浇口残留的尺寸最大不得超过 0.15mm]
- Dimension b does not include dambar protrusion of max 0.100 mm per side.
[尺寸b不包括单边最大0.100 MM的中筋凸出部分]
- Dimensions D and E are the overall extreme outer dimensions of the mold compound. These dimensions exclude mold flash, lead flash, protrusions and burrs but include the maximum allowable mold mismatch.
[D和E是塑封体的外部极限尺寸, 不包括包封溢料、内引线溢料、凸出部分以及胶体毛刺, 但是包含了包封错位的最大尺寸]
- Formed leads shall be planar with respect to one another within a maximum of 0.076 mm relative to the seating plane.
[成型的管脚应为同一平面, 共面性最大为0.1mm]
- ★It is the key size.
[★ 标记为关键尺寸]

■ SOT-323 Soldering Footprint





BC817-16W THRU BC817-40W

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.